

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
19 May 2005 (19.05.2005)

PCT

(10) International Publication Number
WO 2005/044713 A3

(51) International Patent Classification:

B62B 1/00 (2006.01) B60P 1/04 (2006.01)
B62B 1/06 (2006.01) B65F 3/26 (2006.01)
B62B 7/02 (2006.01) B66F 9/06 (2006.01)
B62D 43/00 (2006.01) B66B 9/02 (2006.01)
B60P 1/02 (2006.01)

(21) International Application Number:

PCT/US2004/036728

(22) International Filing Date:

4 November 2004 (04.11.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/517,323 4 November 2003 (04.11.2003) US

(71) Applicant and

(72) Inventor: BURTON, Stewart, S. [US/US]; 47 Rockwood Court, Milford, CT 06460 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): HELLMAN, Robert, R., Jr. [US/US]; 33 Hawley Road, Oxford, CT 06478 (US).


(74) Agent: CROZIER, John, H.; 1934 Huntington Turnpike, Trumbull, CT 06611-5116 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

[Continued on next page]

(54) Title: LIFTING DEVICE AND METHOD



(57) Abstract: In a preferred embodiment, an apparatus, comprising: a column (42) normally generally vertical when a device (30) of which the column (42) is a part is in an operating position; and a platform (62) operatively connected at one end to the column (42) and normally generally horizontal when the device (30) is in an operating position, the platform (62) being selectively raised or lowered to raise or lower a load placed on the platform (62).



FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

(88) Date of publication of the international search report:
27 July 2006